

2" Portable Thermal Printer Series

Feature:

1. Portable device suitable for outdoor usage
2. Low battery indicator, power support 7.4V, 2000mAh
3. Interface: Raw-IR/Bluetooth 2.0 or 4.0/Dual BT(2.0+4.0)/Wifi/RS232/Mini USB
4. Support bluetooth superior function, can take the initiative to search as the main equipment
5. Auto sleep/auto start for power saving, extension use
6. Automatic power-off, energy conservation, humanistic care
7. Support multi-languages

PTP-II



Application:

1. Mobile POS/Retail
2. Parking lot
3. Logistics
4. Ship transport
5. On-site repair/Installation
6. Warehouse/Rear service
7. Utility billing/Meter reading



Specification

MODEL		PTP-II
Print	Printing method	Thermal line printing
	Printing speed	90mm/s(max)
	Resolution	203 dpi
	Effective printing width	48mm
Character	Character Set	ASCII, GB2312-80(Chinese)
	Print Font	ANK: 8x16, 9x17, 9x24, 12x24, 16x18 GBK: 24x24
Paper spec.	Paper Type	Thermal paper
	Paper Diameter	40mm(Max.)
	Paper Thickness	55-90g/m²
	Paper Width	57.5±0.5mm
Paper supply method		Drop-in easy loading
Reliability	TPH	50km
Barcode	1D	EAN-13, EAN-8, CODE39, CODE93, CODE128, CODEBAR, ITF, UPC A, UPC-E
	2D	QR CODE
Text and graphic support		Figure, symbol, graph, curve, icon, multi-languages
Command		Compatible with ESC/POS command set
Sensor		No paper detection function
Interface	Wire	RS232, Mini USB
	Wireless	RAW-IR/Bluetooth 2.0 or 4.0/Wifi/Dual BT(2.0+4.0)
Power		2000mAh 7.4V rechargeable Lithium battery
Recharge adapter		12V, 0.8A adapter
Physical	Weight	222g (Including battery)
	Dimension(WxLxH)	79x112x45mm
	Color	Black/Dark grey/White
Accessories	Standard accessories	Li-ion battery, AC adapter, USB cable, paper roll, user manual
	Optional accessories	Serial cable/CD/Car charger/Protective Case

